

## IC400SC-SO

## Scoop Ice Cream Freezer

## **Product features**

- Sneeze guard in curved glass
- Flat sliding lids with lock
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner
- Flat sliding glass lids with lock
- Optional Scooping baskets for plastic tubs





Scooping basket option

Scoop wash option

## Scoop ice cream freezer with serveover

The IC-SO range is our price friendly basis chest freezer with a serve over glass top. It is a quality scoop ice cream freezer for a fair price. It is perfect if you wish to add scooping ice cream sales to your business and are on a budget.

This model is with flat sliding glass lids with a lock.

The model is still compact and comes in varies sizes, so that it is perfect for both smaller shops and delis with limited space as well as lager shops, gas stations and supermarkets.

It is on wheels and can easily change location in the shop.

It is ideal for branding for better presentation of the cabinet content.

All the different sizes of this range is optimized for baskets that can hold 5 liter plastic tubs in the top and there is room for storage underneath.

Baskets are optional. Type and number must be ordered under accessories.

Design and Material				
SneezeGuard	Yes			
Tempered glass	Yes			
Number of lids	2			
Lid No & Type	2 flat sliding temp. glass lids			
Basket No & Type	Additional (see drawings)			
Castors	4 wheels, 2 with brake			
Exterior Finish	White			
Interior Finish	White painted steel			
Lock	Yes			

Measures and Content					
Temperature Range	°C	-24 to -14			
Climate Class		5			
Gross / Net Weight	kg	130 / 120			
Gross / Net Volume	1	401 / 350			

Cooling and Functions				
Type of Controller		Mechanical		
Type of Cooling		Static		
Type of Defrost		Manual		
Refrigerant		R290		
Refrigerant Charge	g	105		
Thermometer		Yes		
GWP		3		

Power and Consumption	
Energy Class	D
Energy Arrow	D ↑ G

Energy Consumption	kWh/24h	2,2
Annual Energy Consumption	kWh/year	803
EEI		40
EEI Vol	I	319
Input Power	W	141
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	45

Dimensions

Power and Consumption			
Internal Dimension (WxDxH)	mm	1180 x 510 x 655	
External Dimension (WxDxH)	m m	1300 x 630 x 1250	
Packed Dimension (WxDxH)	m m	1400 x 750 x 1130	
40ft Container Load	pcs	50	