

## PDC90

## Black impulse cooler

## **Product features**

- Open top for easy access to products
- Sliding lids are optional
- Glass sides for better presentation of products
- Impressive storage space
- Optimized airflow for stable temperature
- Strong wheels for mobility
- Stainless steel bumper bars
- Not available in Denmark





Sliding glass lids as option

Bumper bars

## Black impulse cooler (island cooler)

Medium sized black impulse cooler ideal as island cooler.

Product visibility is great - all sides are glass - plus it has a high loading line compared to many other similar units.

The PDC range is great for supermarkets, gas stations, convenience stores and cafeterias for e.g berries, fruit, vegetables, sandwiches or other take away.

It has stainless steel bumper bars as standard for protection and easy handling of the cooling unit. Moving it around on the solid castors is easy, so it can easily be moved to a different location in the store.

The design is also optimized for two units to be placed next to each other in a line, if needed.

Cooling is ventilated. Guided airflow makes an even distribution of the cooling effect.

| Design and Material |                         |
|---------------------|-------------------------|
| Lid No & Type       |                         |
| Castors             | 4 castors               |
| Exterior Finish     | Plastified coated steel |
| Interior Finish     | Coated steel            |
| Lock                | No                      |

| Measures and Content |    |           |  |
|----------------------|----|-----------|--|
| Temperature Range    | °C | -1 to +5  |  |
| Climate Class        |    | 3         |  |
| Gross / Net Weight   | kg | 145 / 95  |  |
| Gross / Net Volume   | I  | 153 / 105 |  |
| Total Display Area   | m² | 0,67      |  |

| Cooling and Fund   | tions |            |
|--------------------|-------|------------|
| Type of Controller |       | Electronic |
| Type of Cooling    |       | Ventilated |
| Type of Defrost    |       | Automatic  |
| Refrigerant        |       | R290       |
| Refrigerant Charge | g     | 145        |
| Thermometer        |       | Yes        |
| GWP                |       | 3          |

| Power and Consumption |   |             |
|-----------------------|---|-------------|
| Energy Class          |   | G           |
| Energy Arrow          | G | A<br>↑<br>G |

| Energy Consumption        | kWh/24h  | 6,78       |
|---------------------------|----------|------------|
| Annual Energy Consumption | kWh/year | 2474,7     |
| EEI                       |          | 94,4       |
| Input Power               | W        | 750        |
| Voltage / Frequency       | V/Hz     | 220-240/50 |
| Noise Level               | db(A)    | 50         |

| Dimensions                    |    |                 |
|-------------------------------|----|-----------------|
| Internal Dimension (WxDxH)    | mm | 860 x 555 x 220 |
| External Dimension<br>(WxDxH) | mm | 900 x 845 x 971 |

Power and Consumption

Packed Dimension (WxDxH) mm 930 x 885 x 1185

40ft Container Load pcs 26