

## **IC300SCEB**

## Ice Cream Freezer

## **Product features**

- NEW: Includes full set of baskets
- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- · Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)

## Chest freezer with curved sliding glass lids

The IC-SCEB freezer is a price friendly compact display chest freezer. It is great for start-up companies, season sale etc. It is very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in varies sizes. The many sizes makes the model perfect for smaller shops and delis with limited space as well as larger shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

The SCEB-range is with a lower front than back and curved sliding glass lids. Both features provides a better visual display and presentation of the content. This makes the freezer ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

Design and Material	
Tempered glass	Yes
Number of lids	2
Lid No & Type	2 curved sliding temp. glass lids
No. of baskets	4
Basket No & Type	4 Wire basket, white
Castors	4 wheels, 2 with brake
Exterior Finish	White
Interior Finish	White painted steel
Interior Light	No
Lock	Yes

Measures and Content			
Temperature Range	°C	-24 to -14	
Climate Class		5	
Gross / Net Weight	kg	65 / 57	
Gross / Net Volume	I	264 / 230	

Cooling and Functions			
Type of Controller		Mechanical	
Type of Cooling		Static	
Type of Defrost		Manual	
Refrigerant		R290	
Refrigerant Charge	g	85	
Thermometer		Yes	
GWP		3	

Power and Consumption		
Energy Class		Е
Energy Arrow	E	A ↑ G

Energy Consumption	kWh/24h	
Annual Energy Consumption	kWh/year	814
EEI		52
EEI Vol	I	229
Input Power	W	119
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	45

Dimensions		
Internal Dimension (WxDxH)	mm	890 x 495 x 710

64

40ft Container Load