

PDC125

Black impulse cooler



Product features

- Open top for easy access to products
- Sliding lids are optional
- Glass sides for better presentation of products
- Impressive storage space
- Tilting function for better product display
- Optimized airflow for stable temperature
- Strong wheels for mobility
- Stainless steel bumper bars
- Not available in Denmark



Sliding glass lids as option



Strong castors

Black impulse cooler (island cooler)

Large sized black impulse cooler ideal as island cooler.

Product visibility is great - all sides are glass - plus it has a high loading line compared to many other similar units. Glass lids are optional for the large PDC125 - not for the medium unit.

The PDC range is great for supermarkets, gas stations, convenience stores and cafeterias for e.g berries, fruit, vegetables, sandwiches or other take away.

It has stainless steel bumper bars as standard for protection and easy handling of the cooling unit. Moving it around on the solid castors is easy, so it can easily be moved to a different location in the store.

The design is also optimized for two units to be placed next to each other in a line, if needed.

If on the other hand the unit is placed up against a wall or at the end of an aisle, then PDC125 has a tilting function to an 11 degree angle for better product display.

Cooling is ventilated. Guided airflow makes an even distribution of the cooling effect.

Design and Material		Measures and Content		Power and Consumption		
Lid No & Type		Temperature Range	°C	-1 to +5	Energy Class	G
Castors	4 castors	Climate Class		3	Energy Arrow	
Exterior Finish	Plastified coated steel	Gross / Net Weight	kg	169 / 130	Energy Consumption	kWh/24h 9,2
Interior Finish	Coated steel	Gross / Net Volume	l	270 / 235	Annual Energy Consumption	kWh/year 3359,46
Lock	No	Total Display Area	m²	1,31	EEl	93,5
		Cooling and Functions				
		Type of Controller		Electronic	Input Power	W 1178
		Type of Cooling		Ventilated	Voltage / Frequency	V/Hz 220-240/50
		Type of Defrost		Automatic	Noise Level	db(A) 51
		Refrigerant		R290		
		Refrigerant Charge	g	150	Dimensions	

Measures and Content

Thermometer	Yes
GWP	3

Power and Consumption

Internal Dimension (WxDxH)	mm	1210 x 904 x 220
External Dimension (WxDxH)	m	1250 x 1203 x 971
Packed Dimension (WxDxH)	m	1370 x 1190 x 1080
40ft Container Load	pcs	20