



## FS1600H

Display Cooler

### Product features

- Improved product presentation
- 2 internal fans
- Less maintenance
- LED light in door frame
- Adjustable shelves
- Ventilated cooling
- Hinged alu-framed glass doors



LED light inside door frame



Digital thermostat

### 3-door display cooler

FS1600H-P is a perfect choice for stores wanting to utilize their limited space best possible or wanting to reduce energy consumption compared to e.g. open front coolers.

The spiral maintenance free condenser improves the cooling performance together with 2-layered glass and 2 internal fans. It also saves energy and means the unit requires less maintenance.

Door glass, shelves, LED light in the doors and the finish in general has been improved in order to optimize the presentation of the displayed products.

You can for example have different shelf positions per door instead of one big shelf - this gives a more flexible product display. Middle shelves are 535 mm wide. Side shelves in both sides are 465 mm wide.

Our 3-door cooler is well suited for e.g. supermarkets, convenience stores and gas stations, and the black design and improved finish also opens up the possibility for using the cooler in restaurants, cafés or bars.

FS1600H-P also comes in a version with canopy - FSC1600H-P.

| Design and Material |                                   | Measures and Content  |     | Power and Consumption |                           |                 |
|---------------------|-----------------------------------|-----------------------|-----|-----------------------|---------------------------|-----------------|
| No. of Doors        | 3                                 | Cans 330 ml           | pcs | 1386                  | Energy Class              | E               |
| Door No & Type      | 3 hinged self-closing glass doors | Cans 500 ml           | pcs | 770                   | Energy Arrow              |                 |
| Tempered glass      | Yes                               | Bottles 330 ml        | pcs | 734                   | Energy Consumption        | kWh/24h 6,4     |
| Door Reversible     | No                                | Bottles 500 ml PET    | pcs | 734                   | Annual Energy Consumption | kWh/year 2336   |
| No. of Shelves      | pcs 15                            | Temperature Range     | °C  | +2 to +10             | EEL                       | 58              |
| Shelves No & Type   | 15 wire shelves white             | Climate Class         |     | 4                     | Input Power               | W 817           |
| Shelf Color         | White                             | Gross / Net Weight    | kg  | 211 / 206             | Voltage / Frequency       | V/Hz 220-240/50 |
| Shelf Dimensions    | 465/535 x 470 mm                  | Gross / Net Volume    | l   | 1329 / 825            | Noise Level               | db(A) 45        |
| Feet / Legs         | 6 adjustable legs                 | Cooling and Functions |     |                       |                           |                 |
| Castors             | 6 wheels                          | Type of Controller    |     | Electronic            |                           |                 |
| Exterior Finish     | White                             | Type of Cooling       |     | Ventilated            |                           |                 |
|                     |                                   | Type of Defrost       |     | Automatic             |                           |                 |
|                     |                                   | Dimensions            |     |                       |                           |                 |

**Design and Material**

|                 |                     |
|-----------------|---------------------|
| Interior Finish | White painted steel |
| Interior Light  | LED                 |
| Lock            | Yes                 |

**Measures and Content**

|                    |   |      |
|--------------------|---|------|
| Refrigerant        |   | R290 |
| Refrigerant Charge | g | 145  |
| Thermometer        |   | Yes  |
| GWP                |   | 3    |

**Power and Consumption**

|                            |     |                   |
|----------------------------|-----|-------------------|
| Internal Dimension (WxDxH) | m   | 1492 x 585 x 1518 |
|                            | m   |                   |
| External Dimension (WxDxH) | m   | 1600 x 730 x 2073 |
|                            | m   |                   |
| Packed Dimension (WxDxH)   | m   | 1660 x 795 x 2124 |
|                            | m   |                   |
| 40ft Container Load        | pcs | 14                |