


Counter Refrigerated

GCR2254X



Short Description



Product dimensions, HxWxD, mm	835 x 2242 x 700	
Product depth w/handle, mm	700	
Packaging dimensions, HxWxD, mm	1085 x 2353 x 750	
Total packaging volume m3	1,915	
Gross volume, L	581	
Net volume, L	285	
Gross- / Net volume, L	581/285	
Internal dimensions, HxWxD, mm	618 x 1700 x 580	
Gross- / Net weight, kg	174 / 142	
Performance and consumption		
Energy efficiency class	С	
Daily Energy Consumption, kWh/24	3,3	
Annual energy cons. kWh/a	1206	
Energy Efficiency Index (EEI)	47,89	
Noise level, dB(A)	55	

Dimensions and weight

NOISE IEVEI, UD(A)	55
Refrigeration / freezing technique	Ventilated
Climate class	4
Type of refrigerant / gas gr.	R600a / 108
Temperature range °C	-2 / 8

Installation and power	
Voltage / hertz, V/hz	230 / 50
Length of Powercord, cm	300

Design and comfort		
Controller	Digital	
Control panel	Outside	
Digital display	Yes	
Internal light	No light	
External thermometer	Yes	
Reversible door	Yes	
Door- / lid type	Left hinged	
Self closing door	Yes	
Handle	Integrated	
Number of feet	6	
Number of castors, pcs	0	
Lock & Key	No	
Colour and material		
Inside Colour	Stainless Steel	
Colour and material of door/lid	Stainless steel solid	
Interior features		
Number of Shelves	4	
Adjustable shelves	Yes	
Max loading per shelves, kg	40	
Large shelves size WxD, mm	325x530	
Small shelves size WxD, mm	325x530	



dwell position Suitable for GN 1/1 containers .

Key features

Self-closing doors with 120°

Height-adjustable stainless . legs 125-200mm

.

- Epoxy-coated wire shelves max 40 kg capacity
- AISI 304 stainless steel . internally
- . AISI 201 stainless steel externally
- Also available as 60 Hz for • marine / offshore as an order item
- 1 set of door-kit for reversing . the door can be purchased as an additional accessory