



MTF210

Wall Freezer/Cooler

Product features

- Side-to-center ventilated cooling
- Ideal for optimizing store space
- Freezer / Cooler
- Easily switchable between cooler and freezer
- Ideal with chest cooler / freezer underneath
- Heated Self-closing glass doors
- Automatic defrost
- Adjustable legs



LED light inside door frame



Digital thermostat

3-door freezer/cooler wall cabinet for maximizing store space

Save valuable floor space with this brand new MTF model that you can install either as a freezer or cooler; it is perfect for small shops, convenience stores, butchers, supermarkets etc. It has side-to-center ventilation, which makes it possible to stock the cabinet in full depth without affecting the temperature.

Combine the MTF top freezer/cooler with a chest freezer/cooler underneath to maximize product presentation – you can find great options in our range of supermarket freezers/coolers. It provides a variety of options, as it can be placed against a wall or as an island display. The cabinet comes with a fixed base shelf and two adjustable wire shelves that can be tilted, making it easy to stage products nicely to customers.

Design and Material	
No. of Doors	3
Door No & Type	3 self-closing heated glass doors
Tempered glass	Yes
Door Reversible	No
No. of Shelves pcs	9
Shelves No & Type	9 adjustable wire shelves, white
Shelf Color	White
Shelf Dimensions	595x423
Bottom Shelf Dimensions	595x375
Max Load of Shelves kg/m ²	196
Feet / Legs	Strong stand
Exterior Finish	White
Interior Finish	White painted steel
Interior Light	LED

Measures and Content	
Temperature Range °C	-24 to -18 / -1 to +8
Climate Class	4
Gross / Net Weight kg	355 / 288
Gross / Net Volume l	893 / 628
Total Display Area m ²	1,44

Cooling and Functions	
Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic
Refrigerant	R290
Refrigerant Charge g	145
Thermometer	Yes
GWP	3

Power and Consumption	
Energy Class	D
Energy Arrow	
Energy Consumption kWh/24h	16,35
Annual Energy Consumption kWh/year	5971
EEL %	49,4
Input Power W	1040
Voltage / Frequency V/Hz	220-240/50
Noise Level db(A)	58

Dimensions	
Internal Dimension (WxDxH) mm	1980 x 480 x 947
External Dimension (WxDxH) m	2100 x 745 x 2430
Packed Dimension (WxDxH) m	2210 x 780 x 1610
40ft Container Load pcs	16

Design and Material

Lock

No