



## CR1414F

Coldroom (Freezing)

### Product features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Not available in Belgium, France & Germany
- Easy assembly
- Ventilated floor kit as accessory
- Alarm kit as accessory



Strong handle



Cooling unit

Design and Material		Measures and Content		Power and Consumption			
No. of Doors	1	Internal Volume	m <sup>3</sup>	2,8	Energy Consumption	kWh/24h	17,6
Door No & Type	1 hinged solid door	Internal Area	m <sup>2</sup>	1,4	Input Power	W	940
Exterior Finish	Steel panels, polyester coating	Wall thickness	mm	100	Voltage / Frequency	V/Hz	220-240/50
Interior Finish	Steel panels, polyester coating	Density	kg/m <sup>3</sup>	41	Noise Level	db(A)	70
Interior Light	Yes	Temperature Range	°C	-23 to -18	<b>Dimensions</b>		
Lock	Yes	Climate Class		4	Internal Dimension (WxDxH)	m	1240 x 1240 x 1950
		Gross / Net Weight	kg	416 / 394	External Dimension (WxDxH)	m	1440 x 1440 x 2110
		Gross / Net Volume	l	2800 / 2350	Packed Dimension (WxDxH)	m	1000 x 2230 x 2220
<b>Cooling and Functions</b>							
		Type of Controller	Electronic				
		Type of Cooling	Ventilated				
		Type of Defrost	Automatic, hot gas				
		Refrigerant	R455A				