



## CR2323F

Coldroom (Freezing)

### Product features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Not available in Belgium, France & Germany
- Easy assembly
- Ventilated floor kit as accessory
- Alarm kit as accessory



Strong handle



Cooling unit

Design and Material		Measures and Content		Power and Consumption			
No. of Doors	1	Internal Volume	m <sup>3</sup>	8,6	Energy Consumption	kWh/24h	24,4
Door No & Type	1 hinged solid door	Internal Area	m <sup>2</sup>	4,4	Input Power	W	1430
Exterior Finish	Steel panels, polyester coating	Wall thickness	mm	100	Voltage / Frequency	V/Hz	220-240/50
Interior Finish	Steel panels, polyester coating	Density	kg/m <sup>3</sup>	41	Noise Level	db(A)	70
Interior Light	Yes	Temperature Range	°C	-23 to -18	Dimensions		
Lock	Yes	Climate Class		4	Internal Dimension (WxDxH)	m	2140 x 2140 x 1950
		Gross / Net Weight	kg	957 / 935	External Dimension (WxDxH)	m	2340 x 2340 x 2110
		Gross / Net Volume	l	8930 / 8480	Packed Dimension (WxDxH)	m	2420 x 1750 x 2220
Cooling and Functions							
Type of Controller	Electronic						
Type of Cooling	Ventilated						
Type of Defrost	Automatic, hot gas						
Refrigerant	R455A						